

In-Adapter Ferrule cleaner AFC-3000

Features:

- ◆ Superior Cleaning
- ◆ Innovative Technology
- ◆ Battery powered
- ◆ Portable
- ◆ Automated Operation
- ◆ Fast - Approx. 3 seconds
- ◆ Light Weight
- ◆ Rugged
- ◆ Dry Process
- ◆ Applications

Optical Components


Patch Panel

Test Instrument

Systems



Before



After



- In-Adapter fiber optic connector cleaning
- Disposable cartridge
- 500 cleanings per cartridge
- Removes grease, dust, and other organic & inorganic contaminants
- Constant and effective
- Device can be suited to fit male/female types of connectors & adapters

Ordering Options

AFC-3000	In-Adapter connector cleaner
AFC-3000-C	AFC-3000 including cartridge and one adapter tip of choice
EXT-4	4" extension for use with CFC-600-L (For 2.5mm connectors only)
CFC-600-S	Standard replacement cartridge
CFC-600-L	Long replacement cartridge for use with 4" extension
CFC-600-LC	Replacement cartridge for LC connector
TFC-100M/F	Adapter tip for FC PC/APC connectors (male or female)
TSC-100M/F	Adapter tip for SC PC/APC connectors (male or female)
TST-100M/F	Adapter tip for ST connectors (male or female)
TE2K-100M/F	Adapter tip for E-2000 PC/APC connectors (male or female)
TLC-100M/F	Adapter tip for LC PC/APC connectors (male or female)



Specifications

Cartridge Size Options	2.5mm long, 2.5mm short, 1.25mm
Cleaning Cartridge Capacity	600 cleanings
Operating Noise	≤ 45dbA
Operating Temperature	-10°C □ 40°C
Storage Temperature	-30°C □ 60°C
Power Supply (DC)	2 AA batteries (3V)
Weight	14 oz.

11 New King Street
 White Plains, New York 10604
www.aefosinc.com



Tel: (914) 428-3500
 Fax: (914) 428-3621
 Email: sales@aefosinc.com